

DESCRIPTION

PIEZOELECTRIC ACOUSTIC ELEMENT, ACOUSTIC DEVICE, AND
PORTABLE TERMINAL DEVICE

5 Technical Field

[0001]

 The present invention relates to a piezoelectric acoustic element using
a piezoelectric element as a vibration source, and an acoustic device and a
portable terminal device provided with the piezoelectric acoustic element using
10 the piezoelectric element as the vibration source.

 Background Art

[0002]

 A piezoelectric acoustic element using a piezoelectric element as a
15 vibration source has various advantages, such as being compact, lightweight,
power-thrifty, and does not leak magnetic flux, and therefore is expected to be
used as an acoustic part of a portable terminal device. In particular, since the
mounting volume can be significantly reduced in comparison with the
conventional electromagnetic acoustic element, the piezoelectric acoustic
20 element is considered as one critical technique for further reducing size of
portable telephones.

[0003]

 However, the sound source of the piezoelectric acoustic element is a
vibration plate that bends in accordance with the deformation of the
25 piezoelectric element. Therefore, in order to ensure the sound pressure level
that is required to reproduce sounds, the vibration plate must be bent above
some level and a large vibration plate is required. For example, in the

conventional piezoelectric acoustic element, a vibration plate of 20 [mm] in diameter is required to obtain the sound pressure of 90 [dB] when voltage of 1 [V] is applied to the piezoelectric element, and therefore it causes the piezoelectric acoustic element to lose advantages such as compact and lightweight.

[0004]

Next, the frequency characteristics of the conventional piezoelectric acoustic element are described. The piezoelectric acoustic element has the following problems.

- (1) a basic resonant frequency appears in the audible range,
- (2) a frequency characteristic is included so as to generate an unusual sound pressure near the resonant frequency, and
- (3) since ceramic used as a piezoelectric material for the piezoelectric element has high stiffness, the basic resonant frequency becomes higher and no sufficient sound pressure can be obtained in a low frequency range.

[0005]

In order to reproduce the original sound faithfully, the basic resonant frequency must be adjusted at 500 [Hz] or less. So, Japanese Patent Laid-Open No. 2-127448 discloses the technique in which the carbon plate (expansion graphite plate) is used as the vibration plate to improve the frequency characteristic. Also, it is known that the frequency characteristic is improved to some extent by forming the vibration plate into an ellipse.

[0006]

Next, the frequency - sound pressure characteristic of the conventional piezoelectric acoustic element is described. The conventional piezoelectric acoustic element uses the piezoelectric element as the vibration source, as described above. As the piezoelectric material of the piezoelectric element,

ceramic materials and the like with a small loss of mechanical energy during elastic vibration are usually used. Therefore, very high sound pressure can be obtained near the resonance point, however, the irregular frequency - sound pressure characteristic with a large amplitude change will occur in the frequency range except the resonance point. When the amplitude change of the frequency - sound pressure characteristic is large, only sound at a specific frequency is emphasized, and therefore sound quality will deteriorate. So, Japanese Utility Model Laid-Open No. 63-81495 discloses a technique in which a piezoelectric vibrator is buried in flexible foam to flatten the frequency - sound pressure characteristic. Also, Japanese Patent Laid-Open No. 60-208399 discloses a technique that flattens the frequency - sound pressure characteristic by supporting the outer edge of a thin acoustic element by foam formed with an adhesive layer on the surface thereof.

[Patent Document 1] Japanese Patent Laid-Open No. 2-127448

[Patent Document 2] Japanese Utility Model Laid-Open No. 63-81495

[Patent Document 3] Japanese Patent Laid-Open No. 60-208399

Disclosure of Invention

Problems to be solved by the invention

[0007]

The above problems of (1), (2) can be solved by using the technique disclosed in Japanese Patent Laid-Open No. 2-127448 or by using the ellipse vibration plate, however, the sound pressure characteristic will significantly deteriorate. Also, according to the techniques disclosed in Japanese Utility Model Laid-Open No. 63-81495 and Japanese Patent Laid-Open No. 60-028399, the frequency - sound pressure characteristic can be flatten to some extent. However, the frequency - sound pressure characteristic cannot

be sufficiently improved to such a sufficient extent that the original sound can be reproduced. Also, it causes deterioration in the sound pressure characteristic as a whole. As described above, it is difficult to realize a piezoelectric acoustic element that has an excellent frequency characteristic and frequency sound pressure characteristic while retaining a compact size and featuring low power consumption.

Means to solve the problems

[0008]

The present invention has its as an object the implementation of a piezoelectric acoustic elements that is small and lightweight, is power-thrifty, and is excellent in acoustic characteristics.

[0009]

In order to attain the above object, the piezoelectric acoustic element includes a hollow casing having at least one opening; a piezoelectric element is disposed in the casing and bends when a voltage is applied thereto; and a diaphragm is provided at the opening of the casing, the piezoelectric element and the diaphragm are joined through a vibration transmitting member, the diaphragm vibrates when the piezoelectric element bends, and sounds emerge. One end or both ends of the piezoelectric element in a longitudinal direction may be fixed to an inner surface of the casing directly or through a support member. The support member may be elastic or non-elastic.

[0010]

Two or more diaphragms and vibration transmitting members may be respectively arranged, and two or more diaphragms and/or vibration transmitting members may be mutually different as regards at least one of the following: thickness, materials, and size. Two diaphragms are arranged opposite to each other so that the piezoelectric element is in between them,

and two diaphragms may be joined to the piezoelectric element through respective vibration transmitting members. An elastic plate may be joined to the piezoelectric element, and the elastic plate joined to the piezoelectric element may be joined to the diaphragm through the vibration transmitting member.

[0011]

The piezoelectric element having a laminated structure in which conductive layers and piezoelectric material layers are alternately laminated may be used as a vibration source. Also, as the vibration transmitting member, a spring may be used. Further, as the diaphragm, at least one of these films may be used, polyethylene terephthalate film, polyethersulfone film, polyester film, and polypropylene film.

[0012]

The acoustic device or the portable terminal device according to the present invention is provided with the piezoelectric acoustic element of the present invention.

[0013]

In the piezoelectric acoustic element of the present invention, because the piezoelectric element, as the vibration source, and the diaphragm are joined through the elastic vibration transmitting member, the flexion of the piezoelectric element and the elastic reconstruction of the vibration transmitting member act synergistically and the diaphragm vibrates to a large degree.

Therefore, even if the flexion of the piezoelectric element is small, the diaphragm will vibrate to a large degree to obtain sufficient sound pressure.

Also, even if a diaphragm having a small surface area is used, sufficient sound pressure can be obtained. Accordingly, the piezoelectric acoustic element having excellent sound pressure characteristic and the frequency characteristic

can be realized, while maintaining reduction in size and in thickness, low-power consumption, and low cost. Also, when the piezoelectric acoustic element that has these features is used as an acoustic part in an acoustic device and a portable terminal device, size and thickness reduction, lower power
5 consumption, and higher sound quality can be attained in these devices.
[0014]

The above and other objects, features, and advantages of the present invention may be apparent from the following descriptions and drawings that show examples of the present invention.

10

Brief Description of the Drawings

[0015]

FIG. 1A is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Embodiment 1.

15

FIG. 1B is a longitudinal sectional view showing a vibration displacement state of a diaphragm.

FIG. 1C is a longitudinal sectional view showing a vibration displacement state of a diaphragm.

20

FIG. 2 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Embodiment 2.

FIG. 3 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Embodiment 3.

FIG. 4 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Embodiment 4.

25

FIG. 5 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Embodiment 5.

FIG. 6 is a longitudinal sectional view showing an arrangement of a

piezoelectric acoustic element according to Embodiment 6.

FIG. 7 is a perspective exploded view showing an arrangement of a piezoelectric element arranged in a piezoelectric acoustic element according to Embodiment 7.

5 FIG. 8 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Embodiment 8.

FIG. 9A is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 1.

10 FIG. 9B is a transverse sectional view showing an arrangement of a piezoelectric acoustic element according to Example 1.

FIG. 10 is a perspective exploded view showing an arrangement of a piezoelectric element shown in FIG. 9.

FIG. 11 is a side view showing a vibration transmitting member shown in FIG. 9.

15 FIG. 12A is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 2.

FIG. 12B is a transverse sectional view showing an arrangement of a piezoelectric acoustic element according to Example 2.

20 FIG. 13A is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 3.

FIG. 13B is a transverse sectional view showing an arrangement of a piezoelectric acoustic element according to Example 3.

FIG. 14 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 4.

25 FIG. 15 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 5.

FIG. 16 is a perspective exploded view showing an arrangement of a

piezoelectric element shown in FIG. 15.

FIG. 17 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 6.

FIG. 18 is a perspective enlarged view showing arrangements of a piezoelectric element and an elastic plate shown in FIG. 17.

FIG. 19 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 7.

FIG. 20 is a perspective enlarged view showing arrangements of a piezoelectric element and an elastic plate shown in FIG. 19.

FIG. 21 is a longitudinal sectional view showing an arrangement of a piezoelectric acoustic element according to Example 8.

FIG. 22 is a perspective enlarged view showing a spring shown in FIG. 21.

FIG. 23 is a longitudinal sectional view showing an arrangement of an acoustic element according to Comparative Example 1.

FIG. 24 is a longitudinal sectional view showing an arrangement of an acoustic element according to Comparative Example 2.

FIG. 25 is a longitudinal sectional view showing an arrangement of an acoustic element according to Comparative Example 3.

FIG. 26 is a longitudinal sectional view showing an arrangement of an acoustic element according to Comparative Example 4.

Reference Numerals

[0016]

25	1	piezoelectric acoustic element
	2	bottom surface
	3	opening

	5	casing
	6	support member
	7	piezoelectric element
	8	diaphragm
5	9	vibration transmitting member
	10	upper surface
	11	ceiling surface
	12	space
	13	lower surface
10	15	elastic plate
	16	lower insulating layer
	17	upper insulating layer
	18	conductive layer
	19	piezoelectric material layer
15	20	electrode pad
	21	foamed rubber
	22	upper member
	23	lower member
	25	leg member
20	30	acoustic element
	31	casing
	32	piezoelectric element
	33	support member
	34	bottom
25	35	hole
	36	connection member
	37	vibration plate

38 permanent magnet
 38 voice coil
 40 vibration plate
 41 electrode terminal

5

Best Mode for Carrying Out the Invention

[0017]

(Embodiment 1)

Hereinafter, explanations are given of embodiments of a piezoelectric
 10 acoustic element according to the present invention. Figures 1A to 1C are
 longitudinal sectional views showing schematic arrangements of the
 piezoelectric acoustic element according to the present embodiment. As
 shown in FIG. 1A, piezoelectric acoustic element 1 according to the present
 embodiment has hollow casing 5 formed with opening 3 in bottom surface 2,
 15 piezoelectric element 7 in which one end (fixed end) is fixed to the inner
 surface of casing 5 through support member 6, and diaphragm 8 extended over
 opening 3 of casing 5. The other end (free end) of piezoelectric element 7 is
 joined to diaphragm 8 through vibration transmitting member 9. Both support
 member 6 and vibration transmitting member 9 are made of elastic materials.
 20 Also, space 12, in which (h) is the height, is arranged between upper surface
 10 of piezoelectric element 7 and ceiling surface 11 of casing 5.

[0018]

Piezoelectric element 7 to which a voltage is applied repeats the
 expansion and contraction motion, the expansion and contraction motion of
 25 piezoelectric element 7 is transmitted to diaphragm 8 through vibration
 transmitting member 9, and diaphragm 8 vibrates upward and downward.
 More specifically, as shown in FIG. 1B, piezoelectric element 7, to which
 voltage in the forward or reverse direction is applied, bends upward while being
 pivoted on the fixed end, and diaphragm 8 is deformed in the same direction.

At this time, space 12 functions as a clearance allowing piezoelectric element 7 to deform upward. On the other hand, as shown in FIG. 1C, piezoelectric element 7, to which voltage in the reverse or forward direction is applied, bends downward while being pivoted on the fixed end, and diaphragm 8 is deformed in the same direction. In this way, when alternating voltage is applied to piezoelectric element 7, diaphragm 8 deforms (vibrates) upward and downward continuously, and sounds come out. In this arrangement, in piezoelectric acoustic element 1 according to the present embodiment, piezoelectric element 7 and diaphragm 8 are joined through elastic vibration transmitting member 9. Therefore, vibration transmitting member 9 elastically deforms in accordance with the expansion and contraction motion of piezoelectric element 7, and repulsion is produced. Accordingly, the expansion and contraction motion of piezoelectric element 7 is promoted, the vibration displacement amount of diaphragm 8 is increased, and the sound pressure is improved. Further, since piezoelectric element 7, to which vibration transmitting member 9 is joined, increases in weight, a larger inertial force is exerted during the expansion and contraction motion of piezoelectric element 7, and the basic resonant frequency of sounds that come out are reduced. Additionally, since the fixed end of piezoelectric element 7 is fixed to casing 5 through elastic support member 6 and the free end is joined to diaphragm 8 through elastic vibration transmitting member 9, even if a shock is given to casing 5 by being a dropped or the like, most of the shock is absorbed by support member 6 and/or vibration transmitting member 9, and piezoelectric element 7 avoids being broken.

[0019]

Piezoelectric element 7 shown in FIG. 1 has a layered structure formed by sequentially laminating a lower insulating layer, a lower electrode layer (conductive layer), a piezoelectric material layer, an upper electrode layer

(conductive layer), and an upper insulating layer. When zirconic acid or lead zirconate titanate (PZT) is used as the material of the piezoelectric material layer, warpage after ceramic sintering can be reduced and the reliability of the piezoelectric element is improved. Also, the flattening step, such as polishing, after ceramic sintering, can be omitted, and therefore the cost of manufacturing can be reduced. Further, silver or silver/palladium alloy is used as the material for the electrode layer, sintering distortion can be reduced when the electrode layer and the piezoelectric material layer are integrally sintered, and therefore, the piezoelectric element becomes easy to be manufactured by integrated sintering. Needless to say, as materials for the piezoelectric material layer and the electrode layer, existing materials, except for the above materials, may be selected and used, as appropriate.

[0020]

The conventional piezoelectric acoustic element generates sound that is emphasized at a specific frequency. The reason is that the Q factor is high when the piezoelectric acoustic element is regarded as equivalent to an electric circuit element. Therefore, when diaphragm 8 shown in FIG. 1 is made of a material having a low Q factor, Q factor of the piezoelectric element is restrained, and the frequency can be made average. Also, when diaphragm 8 is made of a material that is resistant to displacement, high sound pressure can be obtained. Further, when diaphragm 8 is made of the material that can be easily to be manufactured, variations on film thickness are reduced, and the quality becomes stable. In view of the above matters comprehensively, a polyethylene terephthalate film (PET film), a polyethersulfone film (PES film), a polyester film (PE film), and a polypropylene (PP film) are suitable to materials for diaphragm 8.

[0021]

(Embodiment 2)

Next, explanations are given of another embodiment of the piezoelectric acoustic element according to the present invention. Figure 2 is a longitudinal sectional view showing a schematic arrangement of a

5 piezoelectric acoustic element according to the present embodiment. As shown in FIG. 2, the basic structure of the piezoelectric acoustic element according to the present embodiment is similar to that of Embodiment 1. The present embodiment is different from Embodiment 1 in following two points. One point is that the fixed end of piezoelectric element 7 is fixed to the inner
10 surface of casing 5 through non-elastic support member 6. The other point is that the free end of piezoelectric element 7 is joined to diaphragm 8.

Incidentally, in piezoelectric acoustic element 1 shown in FIG. 1, diaphragm 8 is joined to any position between the approximate center in the longitudinal direction and the free end of piezoelectric element 7. In piezoelectric element
15 7, in which the fixed end is fixed to casing 5, the amount of displacement of the free end is largest. Therefore, the free end is joined to diaphragm 8, thereby causing diaphragm 8 to vibrate more effectively. In other words, piezoelectric acoustic element 1 according to the present embodiment has the advantage that a sufficient sound pressure can be ensured even if diaphragm 8 has a
20 small surface in area.

[0022]

Based on the above explanations, it can be understood that the variation amount of the free end is further increased and that diaphragm 8 can be vibrated to a large degree when piezoelectric element 7 is lengthened.

25 Also, it can be understood that the length of piezoelectric element 7 and the area of diaphragm 8 are suitably combined, thereby reducing the size of the piezoelectric acoustic element while ensuring required sound pressure.

[0023]

(Embodiment 3)

Next, explanations are given of yet another embodiment of the piezoelectric acoustic element according to the present invention. Figure 3 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to the present embodiment. As shown in FIG. 3, the basic structure of the piezoelectric acoustic element according to the present embodiment is similar to that of Embodiment 1. The present embodiment is different from Embodiment 1 in that both ends of piezoelectric element 7 in the longitudinal direction are fixed to the inner surface of casing 5 through support members 6a, 6b. Piezoelectric acoustic element 1 according to the present embodiment has the same structure as the piezoelectric acoustic element of Embodiment 1 and has the same effects. Further, the piezoelectric acoustic element, characterized in that the both ends of piezoelectric element 7 in the longitudinal direction are fixed to the inner surface of casing 5, has an advantage that the junction strength between piezoelectric element 7 and casing 5 is further improved.

[0024]

As well, there is also an advantage that two support members 6a, 6b are made different in coefficients of elasticity, thickness, areas, and the like, thereby adjusting the basic resonant frequency of sounds that come out. Incidentally, in piezoelectric acoustic element 1, according to the present embodiment, since both ends of piezoelectric element 7 in the longitudinal direction are fixed to casing 5, the approximate center of piezoelectric element 7 in the longitudinal direction is joined to diaphragm 8. However, the junction position between piezoelectric element 7 and diaphragm 8 is not limited to the position shown in FIG. 3.

[0025]

(Embodiment 4)

Next, explanations are given of still another embodiment of the piezoelectric acoustic element according to the present invention. Figure 4 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to the present embodiment. As shown in FIG. 4, the basic structure of the piezoelectric acoustic element according to the present embodiment is similar to that of Embodiment 1. The present embodiment is different from Embodiment 1 in the following two points.

One point is that two independent openings 3a, 3b are formed in bottom surface 2 of casing 5, and diaphragms 8a, 8b are extended over openings 3a, 3b. The other point is that single piezoelectric element 7 is joined to two diaphragms 8a, 8b through two independent vibration transmitting members 9a, 9b, respectively.

[0026]

Piezoelectric acoustic element 1 according to the present embodiment has the same structure as the piezoelectric acoustic element of Embodiment 1 and has the same effects. Further, piezoelectric acoustic element 1, characterized in that piezoelectric element 7 is fixed to two diaphragms 8a, 8b through two independent vibration transmitting members 9a, 9b, respectively, has an advantage that higher sound pressure can be obtained because sounds come out from two diaphragms 8a, 8b. As well, there is also an advantage that two vibration transmitting members 9a, 9b and two diaphragms 8a, 8b are made from different each other in thickness, height, materials, and the like, thereby giving different resonant frequencies to sounds that come out. These advantages indicate that the frequency band of reproducible sound can be enlarged. Also, the advantage that, when a shock is given to casing 5 by

being dropped or the like, the shock is absorbed by the vibration transmitting members and the support members and is not transmitted to the piezoelectric element, is similar to that of the piezoelectric acoustic elements, which are explained above. However, in piezoelectric acoustic element 1 of the present
5 embodiment having two independent vibration transmitting members 9a, 9b, because the shock is dispersed and absorbed by two vibration transmitting members 9a, 9b, safety is further enhanced.

[0027]

(Embodiment 5)

10 Next, explanations are given of still another embodiment of the piezoelectric acoustic element according to the present invention. Figure 5 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to the present embodiment. As shown in FIG. 5, piezoelectric acoustic element 1 according to the present
15 embodiment is similar to the piezoelectric acoustic element of Embodiment 4 in that diaphragms 8a, 8b are extended over two openings 3a, 3b formed in casing 5. The present embodiment is different from Embodiment 4 in that two openings 3a, 3b are formed on different surfaces of casing 5. Incidentally, the present embodiment is similar to Embodiment 4 in that single piezoelectric
20 element 7 is joined to two diaphragms 8a, 8b through two independent vibration transmitting members 9a, 9b. Therefore, the operations and effects obtained by this arrangement are similar to those of piezoelectric acoustic element of Embodiment 4. However, in piezoelectric acoustic element 1 of the present
25 embodiment, because diaphragms 8a, 8b are arranged at the upper and lower sides (both sides) of piezoelectric acoustic element 7, piezoelectric acoustic element 7 can be made shorter than the piezoelectric acoustic element of Embodiment 4. Further, when each of diaphragms 8a, 8b has the same

surface area, the space that is necessary to arrange two diaphragms 8a, 8b can be smaller than that of the diaphragms 8a, 8b according to Embodiment 4.

[0028]

The surface areas of diaphragms 8a, 8b arranged in piezoelectric
5 acoustic element 1 shown in FIGs. 4 and 5 are smaller those that of
piezoelectric acoustic element 1 shown in FIG. 1 (piezoelectric acoustic
element 1 having one diaphragm 8). However, in piezoelectric acoustic
element 1 shown in FIGs. 4 and 5, since two diaphragms 8a, 8b vibrate
simultaneously, the same level of sound pressure can be obtained as in
10 piezoelectric acoustic element 1 shown in FIG. 1 or the like.

[0029]

(Embodiment 6)

Next, explanations are given of still another embodiment of the
piezoelectric acoustic element according to the present invention. Figure 6 is
15 a longitudinal sectional view showing a schematic arrangement of a
piezoelectric acoustic element according to the present embodiment. As
shown in FIG. 6, piezoelectric acoustic element 1 according to the present
embodiment is similar to the piezoelectric acoustic element of Embodiment 1.
The present embodiment is different from Embodiment 1 in that elastic plate 15
20 is arranged on the bottom surface of piezoelectric acoustic element 7.
Piezoelectric acoustic element 1 of the present embodiment has the same
basic arrangement as piezoelectric acoustic element 1 of Embodiment 1, and
has the same operations and effects.

[0030]

25 However, piezoelectric acoustic element 7, which is integrated with
elastic plate 15, appears to have a lower degree of stiffness, compared to the
same kind of piezoelectric elements that do not have any elastic plate 15, and

therefore, the amount of displacement increases with bending. In other words, piezoelectric element 7 shown in FIG. 6 can causes diaphragm 8 to vibrate to a large degree than the same kind of piezoelectric elements having no elastic plate 15. In view of these points, the thickness of elastic plate 15 preferably occupies one-eighth or more of the total of the thickness of piezoelectric element 7 and the thickness of elastic plate 15. Also, since piezoelectric element 7, with which elastic plate 15 is integrated, is increased in weight in comparison with the same kind of piezoelectric elements having no elastic plate 15, a larger inertial force is applied when piezoelectric element 7 bends, and the basic frequency of sounds that come out is further reduced.

[0031]

Also, when elastic plate 15 is made of a material having a larger mass, such as metal, a still larger inertial force can be applied while piezoelectric element 7 bends, and therefore the basic frequency is further reduced. This indicates that the displacement amount of piezoelectric element 7 and the resonant frequency of sounds that come out can be adjusted without changing the size and the shape of expensive piezoelectric ceramic by adding inexpensive elastic plate 15 to piezoelectric element 7. Additionally, piezoelectric element 7 with which elastic plate 15 is integrated, is improved in durability, and it is difficult for cracks and the like to occur. As a material for metal elastic plate 15, for example, brass is suitable.

[0032]

When a plate spring having a high coefficient of elasticity is used as elastic plate 15, the apparent elasticity of piezoelectric element 7 is increased, and the displacement amount of piezoelectric element 7, while the voltage is applied, is increased. Also, when a slit is formed in the plate spring, the apparent elasticity of piezoelectric element 7 is further increased and the

junction area between the plate spring and piezoelectric element 7 is reduced, and therefore manufacturing becomes easy.

[0033]

(Embodiment 7)

5 Next, explanations are given of still another embodiment of the piezoelectric acoustic element according to the present invention. The basic arrangement of the piezoelectric acoustic element according to the present embodiment is similar to the piezoelectric acoustic element of Embodiment 1. The present embodiment is different from Embodiment 1 in the structure of
10 piezoelectric element 7 as a vibration source. Figure 7 schematically shows an arrangement of a piezoelectric element arranged in a piezoelectric acoustic element according to the present embodiment. Piezoelectric element 7 has a multi-layered-structure (laminated structure) in which conductive layers 18 and piezoelectric material layers 19 are alternately laminated between lower
15 insulating layer 16 and upper insulating layer 17. It is known that piezoelectric element 7 of the multi-layered structure, as shown in FIG. 7, is power-thrifty and has a larger vibration displacement amount than piezoelectric element 7 of Embodiment 1. Therefore, the piezoelectric acoustic element of the present embodiment has an advantage that a sufficient sound pressure can be
20 obtained using less power. Also, piezoelectric element 7 shown in FIG. 7 is prevented from being displaced or bent during sintering by the sintering promotion effects of the conductive layer material when being manufactured. Therefore, high flatness is provided without applying another flattening process, and elastic plate 15 shown in FIG. 6 or the like can be joined with no
25 interspace.

[0034]

(Embodiment 8)

Next, explanations are given of still another embodiment of the piezoelectric acoustic element according to the present invention. Figure 8 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to the present embodiment. As shown in FIG. 8, piezoelectric acoustic element 1 according to the present embodiment is similar to the piezoelectric acoustic element of Embodiment 1. The present embodiment is different from Embodiment 1 in that vibration transmitting member 9 is a coil spring shaped like circular cone. Piezoelectric acoustic element 1 of the present embodiment has the same basic arrangement as piezoelectric acoustic element 1 of Embodiment 1, and has the same operations and effects. Further, coil spring 9 repeats energy storage and energy release in accordance with the expansion and contraction motion of piezoelectric element 7, whereby the expansion and contraction motion of piezoelectric element 7 is promoted. Accordingly, piezoelectric acoustic element 1 of the present embodiment has an advantage that the vibration displacement amount of diaphragm 8 is large and sound pressure is high. Also, the shock caused when casing 5 or the like is dropped is absorbed by coil spring 9, and piezoelectric element 7 is prevented from being broken. Coil spring 9 may be replaced with a plate spring or a scroll spring. In any case, a spring having a suitable spring coefficient is selected, thereby maximizing the vibration of diaphragm 8 to obtain high sound pressure.

[0035]

(Example 1)

Detailed explanations are given of the piezoelectric acoustic element of the present invention with reference to an example. Figure 9A is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 1, and FIG. 9B is a transverse sectional view.

[0036]

In piezoelectric acoustic element 1 according to the present example, piezoelectric element 7 having an arrangement shown in FIG. 10 is arranged as a vibration source in casing 5 made of polypropylene resin having a thickness of 0.3 [mm]. Lower insulating layer 16 and upper insulating layer 17 of piezoelectric element 7 are 15 [mm] in length, 4 [mm] in width, and 50[μm] in thickness. Piezoelectric material layer 19 is 15 [mm] in length, 4 [mm] in width, and 300 [μm] in thickness. Upper and lower electrode layers (conductive layers) 18 are 3 [μm] in thickness. Therefore, piezoelectric element 7 has outer dimensions of 15 [mm] in length, 4 [mm] in width, and 0.4 [mm] in thickness. Also, lead zirconate titanate (PZT) ceramic is used for lower insulating layer 16, upper insulating layer 17, and piezoelectric material layer 19, and silver/palladium alloy (weight ratio 7:3) is used for electrode layer 18. Further, piezoelectric element 7 is manufactured by the green sheet method and is fired at 1100°C in the atmosphere for two hours. Moreover, a silver electrode having a thickness of 8 [μm] is formed as an external electrode that is used to electrically connect to electrode layer 18. Also, piezoelectric material layer 19 is polarized in the film thickness direction by the polarization process. Electrode pads 20 formed on the surface of upper insulating layer 17 are electrically connected by copper foil having a thickness of 8 [μm]. Further, two electrode terminal leads that are 0.2 [mm] in diameter are drawn from electrode pads 20, which are electrically connected, through a solder portion that is 1 [mm] in diameter and 0.5 [mm] in height.

[0037]

In the piezoelectric acoustic element according to the present example, a corn coil spring shown in FIG. 11 is used as vibration transmitting member 9 that joins piezoelectric element 7 to diaphragm 8. The corn coil spring is 0.4

[mm] in height (h), has a 2 [mm] minimum coil radius (R1), a 4 [mm] maximum coil radius (R2), and is made of a stainless steel wire. Also, as shown in FIG. 9A, the minimum coil radius surface of the coil spring is joined to lower surface 13 of piezoelectric element 7 and the maximum coil radius surface is joined to diaphragm 8 by epoxy adhesive, respectively. Further, diaphragm 8 shown in FIGs. 9A and 9B is a circular polyethylene terephthalate film that is 15 [mm] in diameter and 0.1 [mm] in thickness.

[0038]

Piezoelectric acoustic element 1 having the above structure of the present example, as shown in FIG. 9B, shows a planar shape that approximates an ellipse, and is 23 [mm] in total length (L) and 16 [mm] in total width (W). Also, total height (H) is 1.5 [mm] which is made up of : thickness (0.1 mm) of diaphragm 8 + height (0.4 mm) of corn coil spring 9 + thickness (0.4 mm) of piezoelectric element 7 + height (0.3 mm) of space 12 + thickness (0.3 mm) of casing 5.

[0039]

(Example 2)

Explanations are given of the piezoelectric acoustic element of the present invention with reference to another example. Figure 12A is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 2, and FIG. 12B is a transverse sectional view. In piezoelectric acoustic element 1 according to the present example, piezoelectric element 7, similar to the piezoelectric element of Example 1, is joined to diaphragms 8a, 8b extended over two openings 3a, 3b formed at the upper and lower sides. Diaphragms 8a extended over opening 3a, is a polyethylene terephthalate film having a thickness of 0.1 [mm], and is joined to upper surface 10 of piezoelectric element 7 through a corn coil spring

(0.4 mm in height) as vibration transmitting member 9a. On the other hand, diaphragm 8b, extended over opening 3b, is a polyethylene terephthalate film having a thickness of 0.05 [mm], and is joined to lower surface 13 of piezoelectric element 7 through a corn coil spring (0.2 mm in height) as vibration transmitting member 9b. Incidentally, diameters (10 [mm]) of both diaphragms 8a, 8b are equal.

[0040]

As shown in FIG. 12B, piezoelectric acoustic element 1 according to the present example has substantially the same form as the piezoelectric acoustic element of Example 1. However, diameters of diaphragms 8a, 8b in piezoelectric acoustic element 1 according to the present example are smaller than those of the diaphragms in the piezoelectric acoustic element of Example 1 (surface areas of diaphragms are smaller). Therefore, piezoelectric acoustic element 1 according to the present example is 20 [mm] in total length (L) and 11 [mm] in total width (W). Specifically, piezoelectric acoustic element 1 according to the present example is smaller than the piezoelectric acoustic element according to Example 1. Also, total height (H) is 1.15 [mm] which is made up of : thickness (0.05 mm) of diaphragm 8b + height (0.2 mm) of corn coil spring 9b + thickness (0.4 mm) of piezoelectric element 7 + height (0.4 mm) of corn coil spring 9a + thickness (0.1 mm) of diaphragm 8a.

[0041]

Incidentally, casing 8 and piezoelectric element 7 in piezoelectric acoustic element 1 according to the present example are similar to those of the piezoelectric acoustic element of Example 1. Also, the corn coil spring in piezoelectric acoustic element 1 according to the present example is similar to the corn coil spring in the piezoelectric acoustic element of Example 1 except for size.

[0042]

(Example 3)

Explanations are given of the piezoelectric acoustic element of the present invention with reference to yet another example. Figure 13A is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 3, and FIG. 13B is a transverse sectional view. In piezoelectric acoustic element 1 according to the present example, both ends of piezoelectric element 7 in the a longitudinal direction are joined to foamed rubbers 21, foamed rubbers 21 are joined to support members 6, and support members 6 are joined to the inner surface of casing 5. Specifically, both ends of piezoelectric element 7 in the longitudinal direction are each fixed to casing 5 through foamed rubber 21 and support member 6. Also, lower surface 13 at the approximate center in the longitudinal direction of piezoelectric element 7 is joined to diaphragm 8 through a corn coil spring as vibration transmitting member 9. Space 12 of that is 0.3 [mm] in height is formed between upper surface 10 and ceiling surface 11 of casing 5. Piezoelectric element 7 is manufactured by the same material and the same manufacturing method as the piezoelectric element of Example 1. Also, dimensions of piezoelectric element 7 are 20 [mm] in length, 4 [mm] in width, and 0.4 [mm] in thickness. As corn coil spring 9, the same corn coil spring as Example 1 is used. Further, a circular polyethylene terephthalate film that is 0.1 [mm] in thickness and 18 [mm] in diameter is used as diaphragm 8. Also, the thickness of casing 5 is 3 [mm].

[0043]

As is clear from FIG. 13B, piezoelectric acoustic element 1 of the present has a planar shape that approximates a circle and is 22 [mm] in diameter (L). Also, the total height (H) is 1.5 [mm].

[0044]

(Example 4)

Explanations are given of the piezoelectric acoustic element of the present invention with reference to still another example. Figure 14 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 4. In piezoelectric acoustic element 1 according to the present example, the same kind of piezoelectric element 7 as the piezoelectric element of Example 1 is joined to diaphragms 8a, 8b that extend over openings 3a, 3b formed at the upper and lower sides of casing 5.

Diaphragms 8a, 8b extended over two openings 3a, 3b are polyethylene terephthalate films of 10 [mm] in diameter and 0.05 [mm] in thickness in perfect circles. Also, vibration transmitting member 9a between upper surface 10 of piezoelectric element 7 and diaphragm 8a is a corn coil spring that is 0.2 [mm] in height. Vibration transmitting member 9b between lower surface 13 of piezoelectric element 7 and diaphragm 8b is a corn coil spring that is 0.4 [mm] in height. Piezoelectric element 7 of the present example is manufactured by the same material and by the same manufacturing method as the piezoelectric element of Example 1. Also, the dimensions of piezoelectric element 7 are 12 [mm] in length, 4 [mm] in width, and 0.4 [mm] in thickness. Corn coil springs, as vibration transmitting members 9a, 9b, are similar to the corn coil spring of Example 2. Both ends of piezoelectric element 7 are fixed to the inner surface of casing 5 through foamed rubbers 21 and support members 6, similar to Example 3. Piezoelectric acoustic element 1 has a planar shape that approximates a circle, similar to the piezoelectric acoustic element of Example 3, however, it is 14 [mm] in diameter (L) and 1.1 [mm] in total height (H) and is smaller and thinner than the piezoelectric acoustic element of Example 3.

[0045]

(Example 5)

Explanations are given of the piezoelectric acoustic element of the present invention with reference to still another example. Figure 15 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric

5 acoustic element according to Example 5. Piezoelectric acoustic element 1 according to the present example is characterized in that piezoelectric element 7 shown in FIG. 16 is used. Piezoelectric element 7 shown in FIG. 16 has a multi-layered-structure (laminated structure) in which conductive layers 18 and piezoelectric material layers 19 are alternately laminated between lower

10 insulating layer 16 and upper insulating layer 17. Upper and lower insulating layers 16, 17 and piezoelectric material layer 19 are 16 [mm] in length, 4 [mm] in width, and 40 [μ m] in thickness. Conductive layer 18 is 16 [mm] in length, 4 [mm] in width, and 3 [μ m] in thickness. Also, piezoelectric material layer 19 is eight-layered and conductive layer 18 is nine-layered (for convenience, layers are partially omitted in FIG. 16). Therefore, the dimensions of piezoelectric

15 element 7 are 16 [mm] in length, 4 [mm] in width, and 0.4 [mm] in thickness.

Lead zirconate titanate (PZT) ceramic is used for lower insulating layer 16, upper insulating layer 17, and piezoelectric material layer 19, and silver/palladium alloy (weight ratio 7:3) is used for electrode layer 18. Further,

20 piezoelectric element 7 is manufactured by the green sheet method and is fired at 1100°C in the atmosphere for two hours. Moreover, after a silver electrode that is used to electrically connect each conductive layer 18 is formed, the polarization process is applied to piezoelectric material layer 19, and electrode pads 20 formed on the surface of upper insulating layer 17 are electrically

25 connected by copper foil.

[0046]

The outer shape and size of piezoelectric acoustic element 1 of the

present example are slimmer to those of the piezoelectric acoustic element of Example 1. Specifically, piezoelectric acoustic element 1 has a planar shape that approximates a circle, and is 23 [mm] in total length (L), 1.5 [mm] in total height, and 16 [mm] in total width.

5 [0047]

(Example 6)

Explanations are given of the piezoelectric acoustic element of the present invention with reference to still another example. Figure 17 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 6. In piezoelectric acoustic element 1 according to the present example, metal elastic plate 15 is joined to lower surface 13 of piezoelectric element 7 by epoxy adhesive, and one end of elastic plate 15 is fixed to the inner surface of casing 5 through support member 6. Also, lower surface of another end of elastic plate 15 is joined to diaphragm 8 through a corn coil spring as vibration transmitting member 9. Figure 18 shows an enlarged view of piezoelectric element 7 and elastic plate 15 in piezoelectric acoustic element 1 of the present example. Piezoelectric element 7 has the same laminated structure as the piezoelectric element of Example 5, and is 12 [mm] in length (l_1), 4 [mm] in width (w_1), and 0.4 [mm] in thickness (t_1). Also, elastic plate 15 is 15 [mm] in length (l_2), 4 [mm] in width (w_2), and 0.2 [mm] in thickness (t_2). The material of elastic plate 15 is SUS304.

[0048]

Piezoelectric acoustic element 1 of the present example has a planar shape that approximates an ellipse, similar to the piezoelectric element of Example 1. Also, piezoelectric acoustic element 1 is 23 [mm] in total length (L), 1.7 [mm] in total height (H), and 16 [mm] in total width. The thickness of

elastic plate 15 causes an increase in the total height (H) by 0.2 [mm] in comparison with the piezoelectric acoustic element of Example 1.

[0049]

(Example 7)

5 Explanations are given of the piezoelectric acoustic element of the present invention with reference to still another example. Figure 19 is a longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 7. Piezoelectric acoustic element 1 according to the present example is characterized in that piezoelectric element 10 7 is shorter than the piezoelectric acoustic element of Example 6. Specifically, as shown in FIG. 20, metal elastic plate 15 that is 16 [mm] in length (l_2), 4 [mm] in width (w_2), and 0.2 [mm] in thickness (t_2) is joined to piezoelectric element 7 that is 8 [mm] in length (l_1), 4 [mm] in width (w_1), and 0.4 [mm] in thickness (t_1) by epoxy adhesive. The arrangements, except for piezoelectric element 7, are 15 similar to those of the piezoelectric acoustic element of Example 6.

[0050]

(Example 8)

Explanations are given of the piezoelectric acoustic element of the present invention with reference to still another example. Figure 21 is a 20 longitudinal sectional view showing a schematic arrangement of a piezoelectric acoustic element according to Example 8. Piezoelectric acoustic element 1 according to the present example is characterized in that a spring is used as a vibration transmitting member for joining piezoelectric element 7 and diaphragm 8. This spring is formed by connecting the rim of upper member 22 25 having a disc shape 2 [mm] in diameter and the rim of lower member 23 having a ring shape 4 [mm] in diameter by leg member 25 that has a thin plate shape and has elasticity mainly in the direction indicated by an arrow. Incidentally,

the height of the spring is 0.4 [mm]. The arrangements, except for vibration transmitting member 9, are similar to those of the piezoelectric acoustic element of Example 1, and the total length (L) is 23 [mm], the total height (H) is 16 [mm].

5 [0051]

(Characteristic Evaluation)

Explanations are given of measurement results of the characteristics of the piezoelectric acoustic elements of Examples 1 to 8, which are explained above, and of the characteristics of Comparative Examples 1 to 4. First, the
10 arrangements of Comparative Examples 1 to 4 are outlined, and then explanations are given of the measurement results.

[0052]

(Comparative Example 1)

Figure 23 shows a schematic arrangement of acoustic element 30 of
15 Comparative Example 1. Acoustic element 30 is a piezoelectric acoustic element and has piezoelectric element 32 as the same piezoelectric element of Example 1 located in casing 31 that is formed of the same material and in the same size as the casing of Example 1. One end of piezoelectric element 32 is fixed to the inner surface of casing 31 through the same support member 33 as
20 the support member of Example 1, and the other end is a free end. Also, hole 35 is formed in bottom 34 of casing 31, and sounds are radiated from hole 35 when voltage is applied to piezoelectric element 32.

[0053]

(Comparative Example 2)

25 Figure 24 shows a schematic arrangement of acoustic element 30 of Comparative Example 2. Acoustic element 30 is also a piezoelectric acoustic element and basically has the same arrangement as the acoustic element of

Comparative Example 1. The differences are that both ends of piezoelectric element 32 are fixed to the inner surface of casing 31 and hole 35 is formed at the center of bottom 34.

[0054]

5 (Comparative Example 3)

Figure 25 shows a schematic arrangement of acoustic element 30 of Comparative Example 3. Acoustic element 30 is also a piezoelectric acoustic element and basically has the same arrangement as the piezoelectric acoustic element of Comparative Example 1. The differences are that the free end of
10 piezoelectric element 32 is provided with metal vibration plate 37 through connection member 36.

[0055]

(Comparative Example 4)

Figure 26 shows a schematic arrangement of acoustic element 30 of
15 Comparative Example 4. Acoustic element 30 is an electromagnetic acoustic element having permanent magnet 38, voice coil 39, and vibration plate 40. When a current is input to voice coil 39 through electric terminal 41, a magnetic force is generated, and vibration plate 40 is vibrated by the generated magnetic force to produce sounds.

20 [0056]

(Measurement Result 1)

When the basic resonant frequencies of the piezoelectric acoustic elements of Examples 1 to 8 and the acoustic elements of Comparative Examples 1 to 4 are measured, the following results are obtained.

25 [0057]

Example 1: 443 [Hz]

Example 2: 452 [Hz] and 316 [Hz]

Example 3: 496 [Hz]

Example 4: 491 [Hz] and 320 [Hz]

Example 5: 396 [Hz]

Example 6: 276 [Hz]

5 Example 7: 263 [Hz]

Example 8: 370 [Hz]

Comparative Example 1: 1087 [Hz] or more

Comparative Example 2: 1067 [Hz]

Comparative Example 3: 1027 [Hz]

10 Comparative Example 4: 730 [Hz]

With the above measurement results, it can be understood that the piezoelectric acoustic element of the present invention has a wider frequency band. In particular, it can be understood that the piezoelectric acoustic elements of Examples 2 and 4 have two basic resonant frequencies and the frequency band is enlarged.

[0058]

(Measurement Result 2)

When the sound pressure level is measured while the voltage of 1 [V] is applied to the piezoelectric acoustic elements of Examples 1 to 8 and to the acoustic elements of Comparative Examples 1 to 4, the following results are obtained.

[0059]

Example 1: 96 [dB]

Example 2: 92 [dB]

25 Example 3: 91 [dB]

Example 4: 99 [dB]

Example 5: 107 [dB]

Example 6: 106 [dB]

Example 7: 118 [dB]

Example 8: 97 [dB]

Comparative Example 1: 38 [dB]

5 Comparative Example 2: 57 [dB]

Comparative Example 3: 74 [dB]

Comparative Example 4: 72 [dB]

With the above measurement results, it can be understood that the piezoelectric acoustic element of the present invention can reproduce a very high sound pressure. In particular, the sound pressure level is 91 [dB] when the voltage of 0.5 [V] is applied to the piezoelectric acoustic element of Example 5. In other words, almost the same level of sound pressure that was obtained by the piezoelectric acoustic element in Examples 1 to 3 can be obtained in this case, even though the applied voltage is one-half.

15 [0060]

(Measurement Result 3)

When the sound pressures of the acoustic elements of Examples 1 to 8 and Comparative Examples 1 to 4 at frequencies of 500 [Hz] to 2000 [Hz] are measured and the alienation rate between the maximum sound pressure and the minimum sound pressure is calculated, the following results are obtained.

[0061]

Examples 1 to 8: 25% or less

Comparative Examples 1 to 3: more than 40%

Comparative Example 4: more than 25%, and less than 40%

25 With the above measurement result, it can be understood that the piezoelectric acoustic element of the present invention has a flat sound frequency characteristic.

[0062]

(Measurement Result 4)

When the sound pressure levels are measured before and after a free fall of 50 cm for the piezoelectric acoustic elements of Examples 1 to 8 and the acoustic elements of Comparative Examples 1 to 4, and when the change rate is calculated, the following results are obtained.

[0063]

Examples 1, 2: 3% or less

Example 3: more than 3% ,and 10% or less

10 Examples 4 to 7: 3% or less

Example 8: more than 3% ,and 10% or less

Comparative Examples 1 to 4: more than 10%

With the above measurement result, it can be understood that the piezoelectric acoustic element has excellent shock resistant characteristics.

15 [0064]

(Measurement Result 5)

When the piezoelectric acoustic elements of Examples 1 to 8 and the acoustic elements of Comparative Examples 1 to 4 are continuously driven for 100 hours, and when the sound pressures are measured before and after that, and the change rate is calculated, the following results are obtained.

[0065]

Examples 1, 2: more than 3%, and 10 % or less

Examples 3 to 8: 3% or less

Comparative Examples 1 to 4: 10% or more

25 With the above measurement result, it can be understood that the piezoelectric acoustic element of the present invention has sufficient durability and high reliability.

[0066]

(Measurement Result 6)

When 50 pieces of the piezoelectric acoustic elements for each of Examples 1 to 8 and 50 pieces of the acoustic elements for each of

- 5 Comparative Examples 1 to 4 are respectively manufactured, the sound pressure level is measured when the voltage of 1 [V] is applied to each element, and then the alienation rate between the maximum value and the minimum value is calculated, and the following results are obtained.

[0067]

- 10 Examples 1, 2: 2.5% or less
 Example 3: more than 5%, and 15% or less
 Examples 4 to 7: 5% or less
 Example 8: more than 5%, and 15% or less
 Comparative Examples 1 to 4: more than 15%

- 15 With the above measurement result, it can be understood that variations are small among the manufactured pieces in the piezoelectric acoustic element of the present invention.

[0068]

The above measurement results are summarized in Table 1.

- 20 Incidentally, in measurement result 1, "◎" (very good) is shown when the basic resonant frequency is 300 [Hz] or less, "○" (good) is shown when the basic resonant frequency is more than 300 [Hz] and 500 [Hz] or less, "△" (average) is shown when the basic resonant frequency is more than 700 [Hz], and 1000 [Hz] or less, and "×" (poor) is shown when the basic resonant
 25 frequency is more than 1000 [Hz].

[0069]

In measurement result 2, "◎" is shown when the sound pressure level

is more than 90 [dB], and "×" is shown when the basic resonant frequency is 90 [dB] or less.

[0070]

In measurement results 3 and 6, "○" is shown when the alienation rate
5 is 25% or less, "△" is shown when the alienation rate is more than 25%, and
40% or less, and "×" is shown when the alienation rate is more than 40%.

[0071]

In measurement results 4 and 5, "○" is shown when the sound
pressure change is 3% or less, "△" is shown when the sound pressure change
10 is more than 3%, and 10% or less, and "×" is shown when the sound pressure
change is more than 10%.

[0072]

In measurement result 6, "○" is shown when the alienation rate is 5%
or less, "△" is shown when the alienation rate is more than 5%, and 15% or
15 less, and "×" is shown when the alienation rate is more than 15%.

[0073]

[Table 1]

	Measurement Result 1	Measurement Result 2	Measurement Result 3	Measurement Result 4	Measurement Result 5	Measurement Result 6
Example 1	O(443Hz)	O(96dB)	O	O	Δ	O
Example 2	O(452Hz) O(316Hz)	O(92dB)	O	Δ	Δ	O
Example 3	O(496Hz)	O(91dB)	O	O	O	Δ
Example 4	O(491Hz) ⊙(320Hz)	O(99dB)	O	O	O	O
Example 5	O(406Hz)	O(107dB)	O	O	O	O
Example 6	⊙(276Hz)	O(106dB)	O	O	O	O
Example 7	⊙(263Hz)	O(118dB)	O	O	O	O
Example 8	O(370Hz)	O(97dB)	O	O	O	Δ
Comparative Example 1	x(1087Hz)	Δ(38dB)	x	x	x	x
Comparative Example 2	x(1067Hz)	x(52dB)	x	x	x	x
Comparative Example 3	x(1027Hz)	x(74dB)	x	x	x	x
Comparative Example 4	Δ(730Hz)	x(72dB)	Δ	x	x	x

When the above explanations and measurement results 1 to 6 are considered, it can be understood that the piezoelectric acoustic element of the present invention has various advantages, such as reduced in thickness and size, low voltage drivability, high sound pressure reproducibility, wide frequency characteristic, low cost, and high reliability.

[0074]

Also, it can be understood that the piezoelectric acoustic element of the present invention is available for a broad range of applications including acoustic devices and portable terminal devices. For example, when the piezoelectric acoustic element of the present invention is arranged in an acoustic device, a small and high-quality acoustic device can be attained. Also, when the piezoelectric acoustic element of the present invention is arranged, instead of an electromagnetic acoustic element used in conventional mobile telephones or PDAs (Personal Digital Assistants), higher sound quality can be obtained while attaining size reduction and extending operating time in mobile telephones and PDAs.

[0075]

While preferred embodiments of the present invention have been described using specific terms, such description is for illustrative purposes only, and it is to be understood that changes and variations may be made without departing from the spirit or scope of the following claims.